



THE PROFESSIONALS' CHOICE FOR ACOUSTICAL TILE RESTORATION

TECH DATA SHEET

ProCoat Acoustical Tile & Ceiling Cleaner
Distribution
Manufacturing

ProCoat Products, Inc
Research
Development

CSI DIVISION 9

ProCoat Products, Inc
Research
Development

ProCoat Acoustical Tile & Ceiling Cleaner
Manufacturing
Distribution

CSI DIVISION 9

1. PRODUCT NAME

ProCoat Acoustical Tile and Ceiling Cleaner

2. MANUFACTURER

ProCoat Products, Inc.
260 Centre Street, Suite D
Holbrook, MA 02343
PH: 781-767-2270
FAX: 781-767-2271

3. PRODUCT DESCRIPTION

ProCoat Acoustical Tile & Ceiling Cleaner is a custom two-part detergent based solution. Easily applied, **ProCoat Acoustical Tile & Ceiling Cleaner** can be used on all porous and non-porous wall and ceiling surfaces.

- Approximately 750 square feet per gallon.
- Acoustical qualities of ceiling is maintained.
- No chlorine and odorless once dry.

4. APPLICATION

Area/Ceiling Preparation

- Covering: **ProCoat Acoustical Tile & Ceiling Cleaner** requires minimum area preparation. Protect against spray mist in the air, using **ProCoat Polycover** to cover paper, natural fibers, glass and waxed floor surfaces.
- Remove loose dust/soot from ceiling surface using soft sweep broom or vacuum, remove loose ceiling particles, moving from the outside to the source; i.e., (air diffusers).

5. PRODUCT PREPARATION

- Shake an 8 oz. Bottle of **ProCoat Acoustical Tile & Ceiling Cleaner Concentrate** and then pour into a one gallon container.
- Add one 8 oz bottle of **ProCoat Acoustical Tile & Ceiling Cleaner Activator** into same container.
- Fill remainder of container with distilled or de-ionized water.
- Shake or stir until thoroughly mixed.

6. EQUIPMENT

- **ProCoat Acoustical Tile & Ceiling Cleaner** may be applied using any ceiling spray system at approximately 50 psi.

7. TEMPERATURE.

- **ProCoat Acoustical Tile & Ceiling Cleaner** can be affected by temperature.
- Keep from freezing

8. SAFETY NOTES

- All personnel in the immediate work area should wear goggles and respirators.
- Do not take internally.
- For commercial use only. KEEP OUT OF REACH OF CHILDREN. Avoid direct contact with eyes. For eyes, flush with water.
- if swallowed, dilute with milk and water.
- Do not store the mixed solution in a tightly closed container.

9. PROCEDURE

- Overlap spray passes to ensure even product distribution.
- On walls, start at the bottom and proceed upward. Mist cleaner onto entire ceiling. Wipe down all non-porous surfaces completely. Use sponges and rinse them frequently in clean water.

10. PRODUCT ORIENTATION

- ProCoat distributors and/or manufacturer representatives can provide direction with respect to:
- Cost effective application
- Recommended equipment
- Marketing/Sales strategies
- Job bidding/cost estimating
- Product availability

11. TECHNICAL DATA

More specific information, beyond which is provided below, can be made available upon request.

Mixed:

- Physical Form: Clear Liquid
- Weight: 10lbs. Per Gallon
- Specific Gravity: 1.00