



THE PROFESSIONALS' CHOICE
FOR ACOUSTICAL TILE RESTORATION

TECH DATA SHEET

ProCoat Products, Inc
Research
Development
Manufacturing
Distribution

1. **PRODUCT NAME**

ProCoat Polystick Wide Web Heavy Duty Adhesive Spray

2. **MANUFACTURER**

ProCoat Products Inc.
260 Centre Street, Suite D
Holbrook, MA 02343
PH: (781)767-2270
FAX: (781) 767-2271
www.procoat.com E-mail: info@procoat.com

3. **PRODUCT SUMMARY**

This wide web spray pattern aerosol adhesive is effective for both temporary and permanent bonding and is suitable for the toughest of adhesive applications. It is primarily used for sealing the seams of *ProCoat Poly Cover* 1 mil plastic sheeting together. Polystick is used in lieu of tape or inferior adhesive sprays. It is also very effective on materials such as leather, cardboard, most plastics and cloth. This high solids product is ideal for uneven or porous surfaces and is waterproof, flexible and transparent. *ProCoat Polystick* does not contain chlorinated solvents or deplete the ozone.

4. **APPLICATION**

When spraying and for best results keep the spray tip 10-12 inches away from the surface of the plastic. *ProCoat Polystick* Adhesive Spray tacks up immediately.

Before spraying, read the directions on the can regarding product preparation and use as well as what to do prior to storing a partially used canister.

5. **SAFETY NOTES**

Contains Acetone and Heptane. Extremely Flammable. Use with adequate ventilation. Keep away from heat, sparks, open flames or other ignition sources. Harmful or fatal if swallowed. Do not induce vomiting. Contact a physician immediately. Vapor harmful. Avoid inhalation of spray mist or vapors. If overcome, move patient to fresh air. Call a physician immediately. Eye irritant. Avoid contact with eyes and skin. In case of eye contact, flush immediately with water and continue for 15 minutes. If irritation persists, see a physician. For skin contact, wash with soap and water. If irritation persists, call a physician immediately. Contents under pressure. Do not puncture or incinerate container. Do not store at temperature above 120 F. **KEEP OUT OF REACH OF CHILDREN.**

6. **CAS NUMBERS**

Isobutane/Propane Blend 75-28-5/74-98-6; Acetone 67-64-1; Glycerine Ester of Resin 8050-26-8; Heptane 142-82-5; Block Copolymer 25038-32-8.

7. **AVAILABILITY**

Contact ProCoat Products, Inc. to determine the location of the nearest dealer.

ProCoat Products, Inc
Research
Development
Manufacturing
Distribution