



SAFETY DATA SHEET

SECTION 1 - Chemical Product and Company Information

Product Name: PROCOAT ACOUSTICAL TILE RESTORER Product Code: ATR

Manufactured for:	4-Hour Emergency (Spill, Leak, Exposure or Accident):
ProCoat Products, Inc.	INFOTRAC 800-535-5053
260 Centre Street, Suite D	Outside USA, Call Collect 1-800-510-8510
Holbrook, MA 02343	

Product Use: A protective and/or decorative finish or accompanying product (reference label or product data sheet for more information).

Not recommended for: Any other use not detailed on product data sheet or label.

SECTION 2 - Hazards Identification

GHS Ratings:

Flammable aerosol	1	Flammable aerosol class 1
Gas under pressure	Compressed gas	Entirely gaseous at -50°C
Eye corrosive	2A	Eye Irritant: Subcategory 2A, Reversible in 21 days
Mutagen	1B	Known to produce heritable mutations in human germ cells. Sub category 1B, Positive results: In vivo heritable germ cell tests in mammals, Human germ cell tests, in vivo somatic multagenicity tests, combined with some evidence of germ cell mutagenicity.
Carcinogen	1B	Presumed Human Carcinogen, based on demonstrated animal carcinogenicity
Reproductive toxin	2	Human or animal evidence possibly with other information
Aspiration hazard	1	Aspiration Toxicity Category 1: Known (retarded) human evidence - hydrocarbons with kinematic viscosity $\geq 20.5 \text{ mm}^2/\text{s}$ at 40°C.

GHS Hazards

H222	Extremely flammable material
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways
H319	Causes serious eye irritation
H340	May cause genetic defects

GHS Precautions

P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P210	Keep away from heat/sparks/open flames/hot surfaces - No smoking
P211	Do not spray on an open flame or other ignition source
P251	Pressurized container - Do not pierce or burn, even after use

GHS Hazards

H350 May cause cancer

H361 Suspected of damaging fertility or the unborn child

GHS Precautions

P264 Wash any exposed skin thoroughly after handling

P280 Wear protective gloves/protective clothing/eye protection/face protection

P281 Use personal protective equipment as required

P331 Do NOT induce vomiting

P301/ P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

P305+ P351+ IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing

P308+ P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up

P410+ P403 Protect from sunlight. Store in a well ventilated place

P410+ P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F

P501 Do not flush to sewer, watershed or waterway. Dispose of product in accordance with applicable local, county, state and federal regulations.

Signal Word:

Danger

**SECTION 3 - Composition/Information on Ingredients**

Chemical Name/CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
ETHYL ACETATE 141-78-6 20 to 30%	400 ppm TWA; 1400 mg/m ³ TWA	400 ppm TWA	NIOSH: 400 ppm TWA; 1400 mg/m ³ TWA
PROPANE 74-98-6 10 to 20%	1000 ppm TWA; 1800 mg/m ³ TWA	See Appendix F: Minimal Oxygen Content	NIOSH: 1000 ppm TWA; 1800 mg/m ³ TWA
Acetone 67-64-1 10 to 20%	1000 ppm TWA; 2400 mg/m ³ TWA	500 ppm STEL 250 ppm TWA	NIOSH 250 ppm TWA; 590 mg/m ³ TWA
Limestone 1317-65-3 10 to 20%	15 mg/m ³ TWA (total dust); 5 mg/m ³ TWA; (respirable fraction)		NIOSH: 10 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable dust)

Chemical Name/CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Butane 106-97-8 5 to 10%		1000 ppm STEL	NIOSH: 800 ppm TWA: 1900 mg/m3 TWA
Distillates, petroleum, light distillate hydro- treating process, low boiling 68410-97-9 5 to 10%			
Titanium Dioxide 13463-67-7 5 to 10%	15 mg/m3 TWA (total dust)	10 mg/m3 TWA	
2-Btanone, oxime 96-29-7 0.1 to 1.0%			

Section 4 - First Aid Measures

Inhalation:

Remove exposed individual to fresh air and assist breathing if necessary. Seek medical attention,

Eye Contact:

Flush eyes with lukewarm water for 15 minutes. Seek medical attention immediately.

Skin:

Remove contaminated clothing, wash area immediately with soap and water. See physician if irritation persists.

Ingestion:

Rinse mouth out immediately. Drink 1 or 2 glasses of water to dilute. DO NOT induce vomiting. Contact physician or poison control center immediately.

Section 5 - Fire Fighting Measures

Alcohol Foam, CO2, Dry Chemical

Do not puncture or incinerate. Exposure to heat or prolonged exposure to sun may cause container to burst. Do not expose to heat or store at temperatures above 120 degrees F. Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, sparks, heaters, smoking, electrical motors or static discharge distant from handling pot.

Burning may produce oxides of nitrogen and carbon.

Clear fire area of unprotected personnel. Do not enter confined space without helmet, face shield, bunker coat, gloves, rubber boots and a positive pressure NIOSH-approved self-contained breathing apparatus. A water stream can scatter flames. A spray of water may be used to cool closed containers to prevent pressure buildup and possible auto ignition or explosion when exposed to extreme heat. If water is used, fog nozzles are preferable.

Section 6 - Accidental Release Measures

Stay upwind and away from spill or leak unless wearing appropriate equipment. Stop and/or contain discharge if it may be done safely. Keep all sources of ignition away. Ventilate area of spill. Use non-sparking tools for cleanup. Cover with inert material to reduce fumes. Keep out of drains, sewer, or waterways.

If large spill occurs, alert spill response teams. Contact fire authorities. Notify local health and pollution control agencies.

Section 7 - Handling and Storage

Handling:

Personnel should avoid inhalation of vapors. Personal contact with the product should be avoided. Should contact be made, remove saturated clothing and flush affected skin with water. Containers of this material may be hazardous when empty. Since emptied containers retain product residues (vapor, liquid and/or solid), all hazardous precautions given in this sheet must be observed.

Should contact be made, remove saturated clothing and flush affected skin with water. Containers

Storage:

Keep product containers cool, dry and away from sources of ignition. Use and store this product with adequate ventilation. DO NOT SMOKE in or near storage areas.

Section 8 - Exposure Controls/Personal Protection

Chemical Name/CAS No.	OSHA Exposure Limit	ACGIH Exposure Limit	Other Exposure Limits
ETHYLACETATE 141-78-6	400 ppm TWA; 1400 mg/m ³ TWA	400 ppm TWA	NIOSH: 400 ppm TWA; 1400 mg/m ³ TWA
Propane 74-98-6	1000 ppm TWA; 1800 mg/m ³ TWA	See Appendix F: Minimal Oxygen Content	NIOSH: 1000 ppm TWA; 1800 mg/m ³ TWA
Acetone 67-64-1	1000 ppm TWA; 2400 mg/m ³ TWA	500 ppm STEL 250 ppm TWA	NIOSH: 250 ppm TWA; 590 mg/m ³ TWA
Limestone 1317-65-3	15 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable fraction)		NIOSH: 10 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable dust)
Butane 106-97-8		1000 ppm STEL	NIOSH: 800 ppm TWA; 1900 mg/m ³ TWA
Distillates, petroleum, light distillate hydro-treating process, low-boiling 684 10-97-9			
Titanium Dioxide 13463-67-7	15 mg/m ³ TWA	10 mg/m ³ twa	
2-Butanone 96-29-7			

Section 10 - Stability and Reactivity

Stability: Stable under normal conditions.

Materials to Avoid: Strong oxidizing agents

Conditions to Avoid: High heat, sparks, flames, static discharge

Hazardous Decomposition: Oxidation may produce carbon and nitrogen oxides.
Hazardous polymerization will not occur.

Section 11 - Toxicological Information

Mixture Toxicity

Inhalation Toxicity LC50: 358 mg/L

Component Toxicity

96-29-7 2-Butane, oxine

Oral LD50: 930 mg/kg (Rat) Dermal LD50: 0 mg/kg (Rabbit) Inhalation LC50: 20 mg/L (Rat)

Primary Routes of Entry: Inhalation, Skin Contact, Ingestion

Skin:

Skin contact can cause redness, dryness or rash. Prolonged contact can cause irritation, dry skin, cracks and dermatitis.

Ingestion:

Can cause vomiting, nausea, diarrhea, and gastrointestinal irritation.

Inhalation:

Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache possible unconsciousness. High vapor concentrations or prolonged breathing of lower concentrations may result in damage to the liver, kidneys, lungs and blood forming organs. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage.

Eyes:

Can cause irritation, redness, tearing and blurred vision.

Carcinogenicity:

The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing).

CAS Number	Description	% Weight	Carcinogen Rating
106-97-8	Butane	5 to 10%	Butane: EU REACH Present (C) (containing >=0.1% Butadiene)
13463-67-7	Titanium Dioxide	5 to 10%	Titanium Dioxide: NIOSH: potential occupational carcinogen OSHA listed.
68410-97-9	Distillates, petroleum, light distillate, hydro- treating process, low boiling	5 to 10%	Distillates, petroleum, light distillate hydrotreating process, low-boiling: EU REACH: Present (P)

Section 12 - Ecological Information

Ecological Information:

Uncontrolled release of the product may result in contamination of air, ground, waterways, and/or sewers.

Component Ecotoxicity

ETHYLACETATE

96 Hr LC50 Pimephales promelas: 220 - 250 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus mykiss: 484 mg/L (flow-through); 96 Hr LC50 Oncorhynchus mykiss: 352 - 500 mg/L (semi-static); 48 Hr EC50 Daphnia magna: 560 mg/L static.

Component Ecotoxicity

ETHYL ACETATE

LC50 96 h Pimephales promelas 220 - 250 mg/L (flow-through) (EPA); LC50 96 h Oncorhynchus mykiss 484 mg/L (flow-through) (IUCLID); LC50 96 h Oncorhynchus mykiss 352 mg/L [semi-static] (EPA)

Solvent naphtha,
petroleum, light eliphatic

EC50 72 h Pseudokirchneriella subcapitata 4700 mg/L (IUCLID)

Silica amorphous

LC50 96 h Brachydanio rerio 5000 mg/L [static] (IUCLID)
EC50 48 h Ceriodaphnia dubia 7600 mg/L (IUCLID)
EC50 72 h Pseudokirchneriella subcapitata 440 mg/L (IUCLID)

2-Butanone, oxime

LC50 96 h Pimephales 777 - 914 mg/L [flow-through] (EPA); LC50 96 h Poecilia reticulata 760 mg/l [static] (IUCLID)
EC50 48 h Daphnia magna 750 mg/L (IUCLID)
EC50 72 h Desmodesmus subapicatus 83 mg/L (IUCLID)

Section 13 - Disposal Considerations

Do not flush to sewer, watershed or waterway. Dispose of product in accordance with applicable local, county, state and federal regulations. See Section 8 for information on exposure control and necessary personal protective equipment.

Section 14 - Transportation Information

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
DOT	AEROSOLS, FLAMMABLE, (EACH NOT EXCEEDING 11 IN CAPACITY) Freight Class: 70	UN1950		2.1

Section 15 - Regulatory Information

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986):

This product contains the following listed substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute 13463-67-7 Titanium dioxide.

The following ingredients are listed in the TSCA Section 8(b) Inventory (Hydrated forms of chemical substances are exempt from the inventory as mixtures; the anhydrous chemical substances, however, are reportable for the inventory):

96-29-7	2-Butanone, oxime
7631-86-9	Silica, amorphous
106-97-8	Butane
64742-89-8	Solvent naphtha, petroleum. Light aliphatic
13463-67-7	Titanium dioxide
68410-97-9	Distillates, petroleum, light distillate hydrotreating process, low-boiling
1317-65-3	Limestone
141-78-6	ETHYL ACETATE
74-98-6	Propane

US CAA Section 112 Hazardous Air Pollutants (HAPs) List

- None

US EPCRA (SARA Title III) Section 313 - Toxic Chemical:

- None

Hazardous Material Information System (HMIS)

HEALTH	*	3
FLAMMABILITY		4
PHYSICAL HAZARD	1	X
PERSONAL PROTECTION		

HMIS & NFPA Hazardous Rating

Legend

- * = Chronic Health Hazard
- 0 = INSIGNIFICANT
- 1 = SLIGHT
- 2 = MODERATE
- 3 = HIGH

Section 16 - Disclaimer

Date Prepared: 6/29/2021

Date Revised: 2015-05-29

THIS DOCUMENT SUPERSEDES ANY PROVISION CONTAINED IN THE FORMS, LETTERS, AND PAPERS OF YOUR COMPANY. THIS PRODUCT IS DESIGNED AND INTENDED FOR PROFESSIONAL APPLICATION ONLY. ALL PRODUCTS SHOULD BE THOROUGHLY TESTED UNDER APPLICATION CONDITIONS PRIOR TO USE. THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE RELIABLE. HOWEVER, PROCOAT MAKES NO WARRANTY CONCERNING THIS PRODUCT, WHETHER EXPRESS OR IMPLIED. INCLUDING THE WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. UNDER NO CIRCUMSTANCES SHALL PROCOAT BE LIABLE FOR SPECIAL, INCIDENTAL, CONSEQUENTIAL OR ANY OTHER DAMAGES FROM ALLEGED NEGLIGENCE, BREACH OR WARRANTY, STRICT LIABILITY, OR ANY OTHER LEGAL THEORY ARISING OUT OF THE USE OR HANDLING OF THIS PRODUCT. THE SOLE REMEDY OF THE BUYER AND THE SOLE LIABILITY OF PROCOAT FOR ANY CLAIMS SHALL BE LIMITED TO THE BUYER'S PURCHASE PRICE OF THE PRODUCT WHICH IS THE SUBJECT OF THE CLAIM OR THE AMOUNT ACTUALLY PAID FOR SUCH PRODUCT, WHICHEVER IS LESS. TECHNICAL ADVICE FURNISHED BY PROCOAT SHALL NOT CONSTITUTE AN EXPRESS WARRANTY, WHICH IS EXPRESSLY DISCLAIMED. ALL TECHNICAL ADVICE GIVEN AND ACCEPTED AT THE RISK OF THE BUYER.

|

|

|